

EL-9-12V Slim



Bezeichnung	EL-9-12V Slim	
Artikel Nr.	8995180000	
EAN	4044538036809	
Ausgang	Spannung	12V DC
	Strom	max. 0,75A
	Leistung	max. 9W
Eingang	Spannung	110-240V AC
	Frequenz	50/60 Hz
	Strom	0,05A (bei 220V AC)
Material	Polycarbonat	
Farbe	weiß	
Leistungsfaktor	>0,9 (bei 230V AC Vollast)	
Messpunkt T _c	max. +75°C	
Umgebungstemperatur T _a	-20°C ~ +40°C	
Abmessungen (LxBxH)	145x21x19 mm	
Gewicht	60 g	
Anschlussart primär	15 cm Anschlussleitung 2x0,75 mm ² mit offenen Leitungsenden	
Anschlussart sekundär	15 cm Anschlussleitung 2x0,75 mm ² mit offenen Leitungsenden	
Dimmbar	nein	
EMV	EN 55015	
Sicherheitsfunktionen	Abschaltung bei Kurzschluss, Überlast und Übertemperatur	
Prüfzeichen	CE, F, MM	
Einbauhinweis	Einbaugerät nur für die Zwischendecke geeignet	



EL-9-12V Slim



Type	EL-9-12V Slim	
Part no.	8995180000	
EAN	4044538036809	
Output	Voltage	12V DC
	Current	max. 0.75A
	Power	max. 9W
Input	Rated voltage	110-240V AC
	Frequency	50/60 Hz
	Rated current	0.05A (at 220V AC)
Material	polycarbonate	
Colour	white	
Power factor	>0.9 (at 230V AC full load)	
Measuring point T _c	max. +75°C	
Ambient temperature T _a	-20°C ~ +40°C	
Dimensions (LxWxH)	145x21x19 mm	
Weight	60 g	
Connection primary	15 cm connecting cable 2x0.75 mm ² with free, stripped cable ends	
Connection secondary	15 cm connecting cable 2x0.75 mm ² with free, stripped cable ends	
Dimmable	no	
EMI	EN 55015	
Safety functions	shut-off at short-circuit, overload and overheating	
Test marks	CE, F, MM	
Installation note	built-in device only for false ceiling	

