



Technische Eigenschaften "Lautsprecher Serie 4"

TECHNISCHE DATEN

	NV-4IC6	NV-4IC6-ANG	NV-4IC6-DVC	NV-4IC8	NV-4IC8-ANG	NV-4IW6
Frequenz	55 Hz – 20 KHz	55 Hz – 20 KHz	50 Hz – 20 KHz	40 Hz – 20 KHz	40 Hz – 20 KHz	55 Hz – 20 KHz
Impedanz	8 Ohm	8 Ohm	8 Ohm	8 Ohm	8 Ohm	8 Ohm
Kennschalldruckpegel	88 dB	88 dB	88 dB	88 dB	88 dB	88 dB
RMS-Leistung	75 W	75 W	75 W	75 W	75 W	75 W
Peak-Leistung	150 W	150 W	150 W	150 W	150 W	150 W
Material des Tieftöners	Fiberglas	Fiberglas	Fiberglas	Fiberglas	Fiberglas	Fiberglas
Material des Hochtöners	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Gewicht (kg)	3.72	2.01	2.26	4.35	2.58	3.95
Abmessungen des Tieftöners	165 mm	165 mm	165 mm	203 mm	203 mm	165 mm
Abmessungen des Hochtöners	19 mm	19 mm	19 mm	19 mm	19 mm	19 mm
Abmessungen	230 mm	230 mm	230 mm	270 mm	285 mm	220 mm × 300 mm
Ausschnittmaß	205 mm	205 mm	205 mm	246 mm	258 mm	194 mm × 274 mm
Einbautiefe	100 mm	121 mm	100 mm	112 mm	141 mm	83 mm