

SS, Schelle, zweilappig, feuerverzinkt



Material	Temp.
Stahl	-45 °C / +400 °C

feuerverzinkt

Art. Bez.	dn [mm]	kl [St]	KoGr	Art.Nr.
SS 20 FV	20,0	100	19	021 078
SS 25 FV	25,0	100	19	021 079
SS 32 FV	32,0	100	19	021 080
SS 40 FV	40,0	50	19	021 081
SS 50 FV	50,0	50	19	021 082
SS 63 FV	63,0	50	19	021 083


SRAS, Abstandsschelle, feuerverzinkt; mit Edelstahlschrauben



Material	Temp.
Stahl	-45 °C / +400 °C

Art. Bez.	dn [mm]	kl [St]	gr [St]	KoGr	Art.Nr.
SRAS 16 FV	16,0	50	1200	19	099 234
SRAS 20 FV	20,0	50	1200	19	096 296
SRAS 25 FV	25,0	50	1200	19	096 297
SRAS 32 FV	32,0	25	600	19	096 298
SRAS 40 FV	40,0	25	600	19	096 299
SRAS 50 FV	50,0	25	400	19	096 300
SRAS 63 FV	63,0	20	320	19	096 301

FPE, Endtülle; hellgrau (RAL 7035) oder schwarz (RAL 9005), zum Kabelschutz an Rohrkanten



Material
PE

Art. Bez.	dn [mm]	kl [St]	KoGr	Art.Nr.	
				hellgrau	schwarz
FPE 16	16,0	100	19	061 664	101 262
FPE 20	20,0	100	19	064 849	035 425
FPE 25	25,0	50	19	064 850	035 426
FPE 32	32,0	25	19	064 851	035 427
FPE 40	40,0	25	19	064 852	035 428
FPE 50	50,0	25	19	064 853	035 429
FPE 63	63,0	20	19	064 854	035 430