


Pressverbinder DIN 46267 Teil 1

- **Werkstoff: 99,9% Elektrolyt-Kupfer, geglühtes Material**
- **Oberfläche: verzinkt**
- **für zugentlastete Verbindungen**
- **Pressmarkierung**



Art. Nr.	LQ	KZ	d1	d4	v1	v2	GL	kg/100	VE	VE
291521	6	5	3,8	5,5	2	-	30	0,300	1600	100
291523	10	6	4,5	6,0	2	-	30	0,600	1000	100
291525	16	8	5,5	8,5	2	1	50	1,450	300	50
291527	25	10	7,0	10,0	2	1	50	1,600	300	50
291529	35	12	8,2	12,5	2	1	50	3,000	200	50
291531	50	14	10,0	14,5	3	1	55	4,100	100	25
291533	70	16	11,5	16,5	3	1	55	5,400	100	25
291535	95	18	13,5	19,0	4	2	70	8,300	50	25
291537	120	20	15,5	21,0	4	2	70	9,500	50	25
291539	150	22	17,0	23,5	4	2	80	14,200	30	15
291541	185	25	19,0	25,5	4	2	85	16,900	30	5
291543	240	28	21,5	29,0	5	2	90	22,600	20	10
291545	300	32	24,5	32,0	-	2	100	29,700	10	5
291547	400	38	27,5	38,5	-	3	150	74,000	8	8
291549	500	42	31,0	42,0	-	3	160	89,100	5	5
291551	625	44	34,5	44,0	-	3	160	79,000	1	1
291553	800	52	40,0	52,0	-	3	200	151,300	1	1
291555	1000	58	44,0	58,0	-	3	1000	198,000	1	1

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- 31
- 32
- 33
- 34
- 35
- 36
- 37