


Sockel für TSRM-Schaltschränke

Farbe: RAL 7022, Zerlegbare Ausführung, mit abnehmbarem Deckel (für Kabeldurchführungen und Schrankbefestigung).

Sockel Höhe 100mm (zusammengebaut)

Breite	A (400)	B (600)	C (800)	D (1000)	E (1200)	F (1500)
Tiefe 400	S-A 100/400	S-B 100/400	S-C 100/400	S-D 100/400	S-E 100/400	S-F 100/400
	102,02	96,35	113,35	133,76	141,69	226,70
Tiefe 500	S-A 100/500	S-B 100/500	S-C 100/500	S-D 100/500	S-E 100/500	S-F 100/500
	102,02	96,35	113,35	133,76	141,69	226,70
Tiefe 600	S-A 100/600	S-B 100/600	S-C 100/600	S-D 100/600	S-E 100/600	S-F 100/600
	108,81	99,75	115,62	136,02	143,95	249,37
Tiefe 800	S-A 100/800	S-B 100/800	S-C 100/800	S-D 100/800	S-E 100/800	S-F 100/800
	111,08	100,88	117,89	140,56	148,49	255,04
Tiefe 1000	S-A 100/1000	S-B 100/1000	S-C 100/1000	S-D 100/1000	S-E 100/1000	S-F 100/1000
	138,29	126,95	145,09	167,76	176,83	290,25
Tiefe 1200	S-A 100/1200	S-B 100/1200	S-C 100/1200	S-D 100/1200	S-E 100/1200	S-F 100/1200
	163,22	149,62	173,43	204,03	216,50	346,91



Sockel Höhe 200mm (zusammengebaut)

Breite	A (400)	B (600)	C (800)	D (1000)	E (1200)	F (1500)
Tiefe 400	S-A 200/400	S-B 200/400	S-C 200/400	S-D 200/400	S-E 200/400	S-F 200/400
	112,22	105,98	124,68	147,12	155,86	249,37
Tiefe 500	S-A 200/500	S-B 200/500	S-C 200/500	S-D 200/500	S-E 200/500	S-F 200/500
	112,22	105,98	124,68	147,12	155,86	249,37
Tiefe 600	S-A 200/600	S-B 200/600	S-C 200/600	S-D 200/600	S-E 200/600	S-F 200/600
	119,69	109,73	127,18	149,62	158,36	272,04
Tiefe 800	S-A 200/800	S-B 200/800	S-C 200/800	S-D 200/800	S-E 200/800	S-F 200/800
	122,19	110,97	129,68	154,61	163,33	277,71
Tiefe 1000	S-A 200/1000	S-B 200/1000	S-C 200/1000	S-D 200/1000	S-E 200/1000	S-F 200/1000
	152,12	139,65	159,59	184,53	194,51	317,39
Tiefe 1200	S-A 200/1200	S-B 200/1200	S-C 200/1200	S-D 200/1200	S-E 200/1200	S-F 200/1200
	179,55	164,59	190,77	224,43	238,14	380,92

Ausgleichssockel für TSRM-Schaltschränke

Bei Verwendung des neuen TSRM-Standschranks in Verbindung mit der Schrank-Bauart SRM Farbe: RAL 7035, Höhe 50mm, dient als Ausgleichssockel für den Höhenunterschied 2000 > 2050mm.



Breite	A (400)	B (600)	C (800)	D (1000)	E (1200)
Tiefe 400	ZW-SO A/400	ZW-SO B/400	ZW-SO C/400	ZW-SO D/400	ZW-SO E/400
	51,01	48,17	56,68	66,87	70,85
Tiefe 500	ZW-SO A/500	ZW-SO B/500	ZW-SO C/500	ZW-SO D/500	ZW-SO E/500
	51,01	48,17	56,68	66,87	70,85
Tiefe 600	ZW-SO A/600	ZW-SO B/600	ZW-SO C/600	ZW-SO D/600	ZW-SO E/600
	54,41	49,87	57,81	68,01	71,98
Tiefe 800	ZW-SO A/800	ZW-SO B/800	ZW-SO C/800	ZW-SO D/800	ZW-SO E/800
	55,54	50,44	58,94	70,27	74,25
Tiefe 1000	ZW-SO A/1000	ZW-SO B/1000	ZW-SO C/1000	ZW-SO D/1000	ZW-SO E/1000
	69,14	63,48	83,88	83,88	88,41