



Stahldraht-Spannseil



Stahldraht-Spannseil in verzinkter Ausführung mit Fasereinlage (Hanfseele).
Seil Ø 2 - 6 mm: Rundlitzenseil 6 x 7 nach DIN 3055.
Seil Ø 8 - 10 mm: Rundlitzenseil 6 x 19 nach DIN 3060.
Mindestbruchkraft 1770 N/mm².

Typ	Seil- durch- messer mm	Bruch- last kN	in Ringen m	Verp. m	Gewicht kg/100 m	Art.-Nr.
957 2 G	2	2,35	50	50	1,430	5303202
957 3 G	3	5,29	50	50	3,220	5303206
957 4 G	4	9,41	50	50	5,720	5303214
957 5 G	5	14,7	50	50	8,940	5303222
957 6 G	6	21,1	50	50	12,900	5303230
957 8 G	8	34,8	50	50	22,900	5303257
957 10 G	10	54,4	50	50	35,700	5303265
957 2 A4	2	2,35	50	50	1,430	5303179
957 3 A4	3	5,29	50	50	3,220	5303182
957 4 A4	4	9,41	50	50	5,720	5303185
957 5 A4	5	14,7	50	50	8,940	5303188
957 6 A4	6	21,1	50	50	12,900	5303191
957 8 A4	8	34,8	50	50	22,900	5303194
957 10 A4	10	54,4	50	50	35,700	5303197

Abmessungen



St Stahl **V4A** Edelstahl, rostfrei A4
G galvanisch verzinkt