


- für zugentlastete Verbindungen von Al-Leitern DIN 28201, Teil 1
- Al-Seile nach DIN EN 50182, Cu-Leiter nach DIN 48201
- Werkstoff: Al 99,5%, DIN 40501, E-Cu DIN 40500
- Oberfläche: blank gebeizt • Pressmarkierung • inkl. Kontaktfett

Art. Nr.	LQ rm/sm	rm/sm CU	se	GL	Cu	Al	KZ Cu	KZ Al	kg/100		VE
293578	25	16	35	61	5,5	7,6	8	12	1,600		10
293582	35	16	50	71	5,5	8,0	8	14	2,100		10
293584		25		71	7,0	8,0	10	14	2,500		10
293598	50	25	70	71,5	7,0	9,8	10	16	3,100		10
293600		35		71,5	8,2	9,8	12	16	3,300		10
293606	70	25	95	79	7,0	11,2	10	18	4,400		10
293608		35		79	8,2	11,2	12	18	5,500		10
293610		50		85	10,0	11,2	14	18	5,700		10
293622	95	35	120	79	8,2	13,2	12	22	6,000		5
293624		50		85	10,0	13,2	14	22	8,900		5
293626		70		87	11,5	13,2	16	22	8,200		5
293634	120	50	150	87	10,0	14,7	14	22	7,900		5
293636		70		89	11,5	14,7	16	22	9,500		5
293638		95		97	13,5	14,7	18	22	10,000		5
293652	150	95	185	107,5	13,5	16,3	18	25	11,700		5
293654		120		107,5	15,5	16,3	20	25	14,200		5
293656		150		124,0	17,5	16,3	22	25	16,700		5
293664	185	120	240	108	15,5	18,3	20	28	16,930		5
293666		150		113	17,0	18,3	22	28	19,500		5
293678	240	150	300	124	17,0	21,0	22	32	23,300		5
293680		185		127	19,0	21,0	25	32	25,500		5
293688	300	185	400	128	18,5	19,0	25	34	32,700		5
293690		240		128	21,5	23,5	28	34	37,500		5

