

ABB F-series fieldbus adapter modules for ACS350, ACS355, ACS850, ACQ810 and ACSM1

The F-series fieldbus adapter modules are flexible plug-in adapters that provide fast and simple universal connectivity to all major controllers. Universal connectivity means ABB low voltage drives connect to virtually all controller brands and communication networks, allowing users to choose the best network to meet their needs.



Network connectivity of products provides simplified interface for control and management of drives; improving quality, productivity, flexibility and scalability. Fieldbus networks also offer a cost reduction in wiring costs, compared to traditional I/O connections.

Combining these feature-rich adapter modules with ABB's drives offers a powerful drive solution to OEM's and system integrators focused on the food & beverage, material handling, printing, rubber & plastics, and textile industries.

Advantages of network connectivity

- Decreases mechanical and electrical installation time
- More data is available at a lower cost
- Reduces time and cost of machine expansion or relocation
- Remote data access
- Diagnostics provide predictive failure warnings
- Open protocols, connectivity to any major PLC
- Reusability of system software
- Drive parameter setting

Advantages of ABB network connectivity

- Connectivity to virtually any automation architecture
- Fast and simple connectivity
- Products designed and tested to conform to protocol specifications
- Best in class support resources

End user benefits

- Decrease in mechanical and electrical installation cost
- Decrease in down time
- Increase in productivity
- Diminished start-up cost
- Lower maintenance and diagnostic cost

| Fieldbus | Max. devices | Baud rate |
|---------------------|--------------------------|--------------------------|
| CANopen FCAN-01 | 127 | 50 kbit/s - 1 Mbit/s |
| DeviceNet FDNA-01 | 64 | 125 kbit/s - 500 kbit/s |
| EtherNet/IP FENA-01 | Nearly unlimited | 10 / 100 Mbit/s |
| Modbus-RTU FMBA-01 | 247 | 600 bit/s - 115.2 kbit/s |
| Modbus-RTU FSCA-01 | 247 | 600 bit/s - 115.2 kbit/s |
| Modbus-RTU FRSA-00 | 247 | 600 bit/s - 115.2 kbit/s |
| Modbus-TCP FENA-01 | Nearly unlimited | 10 / 100 Mbit/s |
| PROFIBUS DP FPBA-01 | 32/segment, 126 total | 9.6 kbit/s - 12 Mbit/s |
| LonWorks® FLON-01 | 127/subnet, 32 385 total | 78 kbit/s |
| EtherCAT® FECA-01 | 65 535 | 100 Mbit/s |

CANopen: FCAN-01 (+K457)

The adapter module fulfils CiA (CAN in Automation) standard DSP 402 (Device Profile Drives and Motion Control). CANopen device profiles define both direct access to the drive parameters and time critical process data communication.

DeviceNet: FDNA-01 (+K451)

The DeviceNet adapter module acts as a Class 2 slave with predefined master-slave connection set services. These include the Explicit Messaging, the Poll-Response service and the Change of State/Cyclic service. The adapter supports the ODVA AC/DC Drive Functional Profile with additional features and ABB drives profile.

EtherCAT®: FECA-01 (+K469)

The adapter module supports the CANopen DSP 402 (Device Profile Drives and Motion Control) profile or the ABB drives profile. The FECA-01 implements the EtherCAT® state machine, four sync manager channels to control the access to the application memory, two watch dogs and specified EtherCAT® services, addressing modes and FMMUs.

EtherNet/IP: FENA-01 (+K466)

The adapter module acts as an EtherNet/IP server with support for ODVA AC/DC Drive, ABB drives and Transparent profiles. The adapter module supports both explicit messaging where each attribute of a class is set individually and implicit messaging using input and output instances.

LonWorks®: FLON-01 (+K452)

The FLON-01 LonWorks® adapter module includes two objects, a node object and a drive object. The node object is used to control the drive object. The drive object realises the LONMARK® Functional Profile: Variable Speed Motor Drive, version 1.1.

Modbus-RTU: FMBA-01 (+K458) / FSCA-01 / FRSA-00

The adapter module enables the connection of the drive to a RS-485 Modbus-RTU network. Common read/write single and multiple register function codes are supported.

FRSA-00 is a set of 20 adapters.

Modbus-TCP: FENA-01 (+K466)

The adapter module acts as a Modbus/TCP server with support for ABB drives and Transparent profiles. Common read/write single and multiple register function codes are supported.

PROFIBUS DP: FPBA-01 (+K454)

The adapter module supports PROFIBUS DP-V0 and DP-V1 communication. The FPBA-01 automatically detects the telegram type used, and supports both PPO messages 1 to 6 and standard telegrams (STD) 1 and 20. Communication profiles: PROFIdrive, ABB drives, Transparent 16 and Transparent 32 are supported.

For more information please contact:

www.abb.com/drives
www.abb.com/drivespartners

© Copyright 2010 ABB. All rights reserved.
Specifications subject to change without notice.

Compatibility table

| Fieldbus | ACS350 | ACS355 | ACS850 | ACQ810 | ACSM1 |
|---------------------|--------|--------|--------|--------|-------|
| CANopen FCAN-01 | X | X | X | - | X |
| DeviceNet FDNA-01 | X | X | X | X | X |
| EtherNet/IP FENA-01 | X | X | X | X | X |
| Modbus-RTU FMBA-01 | X | X | - | - | - |
| Modbus-RTU FSCA-01 | - | - | X | X | X |
| Modbus-RTU FRSA-00 | X | X | - | - | - |
| Modbus-TCP FENA-01 | X | X | X | X | X |
| PROFIBUS DP FPBA-01 | X | X | X | X | X |
| LonWorks® FLON-01 | - | X | X | X | - |
| EtherCAT® FECA-01 | - | X | X | - | X |