


Al-Presskabelschuhe für zugentlastete Verbindungen

DIN

- Werkstoff: Al-Leiter im Aufbau nach DIN 48201, Teil 5
- Al-Seile nach DIN EN 50182
- Oberfläche: blank
- Pressmarkierung • inklusive Kontaktfett



Al

• sm/se-Leiter müssen rund gedrückt werden

Art. Nr.	LQ	rm/sm	se	M	KZ	d2	d1	v1	v2	I	B	kg/100	VE
292904	16		25	8	12	8,5	5,8	4	2	52,0	18,0	1,400	50
292906				10	12	10,5	5,8	4	2	52,0	18,0	1,400	50
292908	25		35	8	12	8,5	6,8	4	2	60,0	18,0	1,400	50
292910				10	12	10,5	6,8	4	2	60,0	18,0	1,400	50
292912	35		50	10	14	10,5	8,0	5	2	67,0	21,0	2,100	50
292914				12	14	13,0	8,0	5	2	67,0	21,0	2,000	50
292916	50		70	10	16	10,5	9,8	5	2	72,0	25,0	2,700	50
292918				12	16	13,0	9,8	5	2	72,0	25,0	2,700	50
292920	70		95	10	18	10,5	11,2	6	3	86,0	28,0	4,400	40
292922				12	18	13,0	11,2	6	3	86,0	28,0	4,200	40
292924	95		120	10	22	10,5	13,2	6	3	90,0	32,0	6,300	25
292926				12	22	13,0	13,2	6	3	90,0	32,0	6,400	30
292928				16	22	17,0	13,2	6	3	90,0	34,0	6,400	25
292930	120		150	12	22	13,0	14,7	6	3	91,0	32,0	6,700	25
292932				16	22	17,0	14,7	6	3	91,0	34,0	7,000	25
292934	150		185	12	25	13,0	16,3	6	3	103,0	35,0	9,400	20
292936				16	25	17,0	16,3	6	3	103,0	35,0	8,300	20
292938				20	25	21,0	16,3	6	3	103,0	41,0	9,100	20
292940	185		240	12	28	13,0	18,3	6	3	106,0	40,0	11,700	15
292942				16	28	17,0	18,3	6	3	106,0	40,0	11,600	15
292944				20	28	21,0	18,3	6	3	106,0	40,0	12,000	15
292946	240		300	12	32	13,0	21,0	8	3	116,0	45,0	16,900	10
292948				16	32	17,0	21,0	8	3	116,0	45,0	16,900	12
292950				20	32	21,0	21,0	8	3	116,0	45,0	16,200	10



haupa®

... Lösungen, die überzeugen