

Pressverbinder nach DIN 48085, Teil 1

DIN

- Werkstoff: 99,9% Elektrolyt-Kupferrohr, geglähtes Material
- nach DIN 40500, für zugfeste Verbindungen, Freileitungsbau
- Oberfläche: blank gebeizt
- Pressmarkierung



Cu

Art. Nr.	LQ	KZ	d1	d4	v1	v2	GL	kg/100	VE
291440	6	6	3,8	6,5	8	-	65	1,200	50
291442	10	8	4,5	8,5	10	-	80	2,800	50
291444	16	8	5,5	8,5	10	-	95	2,300	50
291446	25	10	7,0	10,0	10	-	95	2,600	50
291448	35	12	8,2	12,5	10	-	95	5,800	25
291450	50	14	10,0	14,5	10	-	110	7,000	25
291452	70	16	11,5	16,5	10	-	110	9,000	25
291454	95	20	13,5	21,0	16	8	145	8,600	10
291456	120	22	15,0	23,5	16	8	160	29,200	10
291458	150	25	16,5	25,5	16	8	180	117,100	10
291460	185	32	18,5	31,5	-	10	260	17,000	5
291462	240	34	21,0	34,5	-	12	310	163,700	5
291464	300	38	23,5	38,5	-	14	360	29,200	5

